

## REINÆRDT Door frame RST-Flush

<i>Manufacturer</i>	: REINÆRDT
<i>Type</i>	: <b>RST-flush</b>
<i>Frame</i>	: ca. 23 mm chipboard veneered / foiled / laminated
<i>Front part</i>	: ca. 16 mm chipboard veneered / foiled / laminated glued to frame work, width 60 mm
<i>Back part</i>	: ca. 16 mm chipboard veneered / foiled / laminated loose, width 60 mm, adjustability +18 mm
<i>Interconnection</i>	: mitre joints, no screw necessary
<i>Finish</i>	: veneer / laminate custom finish
<i>Surface</i>	: 5 coats of acrylic, UV hardened (no emission to environment)
<i>Weight</i>	: 140 mm approx. 19 kg/ 265 mm approx. 27 kg
<i>Bording</i>	: in accordance with EN204-D3
<i>Dimensions</i>	: in accordance with DIN 18 101
<i>Fittings</i>	: strike plate, screwed , interchangeable, prepared for standard DIN lock, hinges, V 3400, nickleplated
<i>Gasket</i>	: standard flexible door seal
<i>Packing</i>	: jambs and framehead separate packed in carton box
<i>Class</i>	: emission class E 1
<i>Special performance</i>	: double rebated frames ( for mounting rebated shelf screws in hinges- + locking plate area)
<i>Special list</i>	: provide for full glass door, double wings, with cross beam (incl. glazing beads) with side parts (incl. glazing beads) with cross beam and side parts (incl. glazing beads), anti-burglar lock plate (SLP-U) with fix plate for heavy doors , passage frame both sides moulding (loose inside)

Changes are subject to the condition

