

REINÆRDT doors WV (white or coloured)

Manufacturer	: REINÆRDT
Type	: WV (white or coloured)
Thickness	: approx. 39 mm
Frame work	: solid wood frame with intensification lath
Core	: close-meshed honeycomb (tubular, solid chipboard)
Shell	: HDF
Finish	:
Edges	: rebated 13 x 25,5 mm / flush, foiled
Edge profile	: carnies, rounded on request
Surface	: 8 coats of acrylic, UV hardened (no emission to environment)
Construction	: in accordance with DIN 68 706, part I; 5-layered
Bording	: in accordance with EN204-D3
Weight	: $\pm 10 \text{ kg/m}^2$ (19 kg/m^2 , 23,5 kg/m^2)
Dimensions	: in accordance with DIN 18 101
Fittings	: BB type mortise lock case, 55 mm bolt, hinges V 0020
Class	: mechanical rating group N, climate category I, soundproofing Rw = approx. 22 dB, (27, 33 dB), emission class E 1
Special types	: 3-layer solid chipboard core (Rw = approx. 40 dB, approx. 26,5 kg/m^2), triple hinges, heavy-duty (hardwood frame, group S)
Options	: window cut-out, air vents, automatic door bottom, spy eye

Changes are subject to the condition

