

REINÆRDT doors Dekoform CPL

<i>Manufacturer</i>	: REINÆRDT
<i>Type</i>	: RD (Dekoform)
<i>Thickness</i>	: approx. 40 mm
<i>Frame work</i>	: solid wood frame with intensification lath
<i>Core</i>	: close-meshed honeycomb (tubular strips, tubular, solid chipboard)
<i>Shell</i>	: fibre board / HDF
<i>Finish</i>	: 0,45 mm laminated
<i>Edges</i>	: rebated 13 x 25,5 mm / flush, foiled
<i>Edge profile</i>	: carries, rounded on request
<i>Construction</i>	: in accordance with DIN 68 706, part I; 5-layered
<i>Bording</i>	: in accordance with EN204-D3
<i>Weight</i>	: 10,2 kg/m ² (19, 23,5 kg/m ²)
<i>Dimensions</i>	: in accordance with DIN 18 101
<i>Fittings</i>	: BB type mortise lock case, 55 mm bolt, hinges V 0020
<i>Class</i>	: mechanical rating group N, climate category I, soundproofing Rw = approx. 22 dB, (24, 27, 33 dB), emission class E 1
<i>Special types</i>	: 3-ply full width core (Rw = approx. 40 dB, approx. 26.5 kg/m ²), triple hinges, heavy-duty (hardwood frame, group S)
<i>Options</i>	: window cut-out, air vents, automatic door bottom, spy eye

Changes are subject to the condition

